## **Declaration of Performance**



XPS-EN 13164-T3-CS(10\Y)200-DS(70,90)-TR400-WL(T)1,5

## **DoP Number:**

1 Unique identification code of the product-type:

2 Identification of the construction product as required under Article 11(4) of the regulation n° 305/2011/EU:

3 Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as

foreseen by the manufacturer:

4 Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) of the regulation n° 305/2011/EU:

5 Name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) of the regulation n° 305/2011/EU:

6 System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the Regulation n° 305/2011/EU:

7 Notified Certification bodies FIW (Forschunginstitut für Wärmeschutz e.v. München) N° 0751 and TUV Hellas (Tüv Nord Group) N° 0654 performed, carried out the determination of the product type, the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control.

## 8 Declared performance according to harmonized standard:

<ul> <li>Declared performance according to narmonized standa</li> </ul>	EN 13104:2012+A1:201			
Essential characteristics	Performance	Unit	Declared performance	
	Thickness	d <sub>N</sub> [mm]	20 - 25	
Thermal Resistance	Thickness Class	Ť	ТЗ	
memarkesistance	Thermal Resistance	$R_D [m^2 K/W]$	see below table	
	Thermal Conductivity	$\lambda_{D}$ [W/m K]	0,033	
Reaction to fire	Reaction to fire	Euroclass	E	
Realease of Dangerous Substances	Realease of Dangerous Substances		NPD	
Acoustic absorption index	Sound absorption	AW	NPD	
Continous glowing combustion	Continous glowing combustion		NPD	
	Long term water absorption by total immersion	WL(T) [vol.%]	1	
Water Permeability	Long term water absorption by diffusion	WD(V) [vol.%]	NPD	
Water vapour permeability	Water vapor diffusion resistance factor MU		50	
Compressive strength	Compressive stress or compressive strength	CS(10/Y) [kPa]	200	
Tensile/Flexural strength	Tensile Strength perpendicular to faces	TR [kPa]	400	
Durability of reaction to fire against heat, weathering, ageing/degradation	Reaction to fire	Euroclass	E	
	Thermal Resistance	R <sub>D</sub> [m <sup>2</sup> K/W]	see below table	
	Thermal Conductivity	λ <sub>D</sub> [W/m K]	0,033	
Durability of thermal resistance against heat, weathering, ageing/degradation	Freeze-thaw resistance after long term water diffusion test	FTCD	NPD	
	Freeze/thaw resistance after long term water absorption by total immersion	FTCI	NPD	
	Dimensional stability under specified temperature and humidity conditions	DS(70,90)	<5%	
	Deformation under specified compressive load and temperature conditions	DLT	NPD	
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep	CC (2/1,5/50)	NPD	

9 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

Thickness	20	25	30	40	50	60
Thermal Resistance	0,60	0,75	0,90	1,20	1,50	1,80

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Name	Stella Chadiarakou
Function	Quality Assurance Manager
Place	Thessaloniki
Date	20/05/2020
Signature	Jour

This product does not contains Hexabromocyclodecane (declaration according to CPR requirement Article 6 Paragraph 5)

## EN 13164:2012+A1:2015

GR-1008-003

Not applicable

0654-CPR-0044

FIBRANxps ETICS GF 20-25

Thermal Insulation Systems

AVCP - System 3, System 2+

Thermal insulation for buildings, External

FIBRAN S.A. 56010, Thessaloniki, Greece